

BAN-LOCK 부착 STS 폴리

S8M0400 (벨트폭 40mm용) W=50mm

폴리				축경 d/D1/L〔mm〕																											
잇수	dp	do	Fo	축경 d	14	15	16	17	18	19	20	22	24	25	28	30	32	35	38	40	42	45	48	50	55	60	65				
				D1	34	35	36	37	38	46	46	46	49	49	54	54	59	59	64	64	74	74	79	79	84	89	94				
				L	63.5	63.5	63.5	63.5	63.5	68	68	68	68	68	68	68	68	68	68	68	74	74	74	74	74	74	74				
				전달 토크 (N・m)	69	74	79	84	89	240	260	285	310	325	365	390	415	455	495	520	990	1060	1130	1180	1300	1410	1530				
19	48.38	47.01	56	클램프 나사수 (축경) ϕ 14~18 3-M5 (축경) ϕ 19~40 4-M6 (축경) ϕ 42~65 4-M8																											
20	50.93	49.56	59																												
21	53.48	52.10	59																												
22	56.02	54.65	62			○	○																								
24	61.12	59.74	68			○	○	○	○																						
26	66.21	64.84	75					○	○	○	○	○																			
28	71.30	69.93	77							○	○	○	○	○	○																
30	76.39	75.02	83									○	○	○	○	○	○														
32	81.49	80.12	89									○	○	○	○	○	○	○	○												
34	86.58	85.21	92												○	○	○	○	○	○	○	○									
36	91.67	90.30	98												○	○	○	○	○	○	○	○									
40	101.86	100.49	108												○	○	○	○	○	○	○	○	○	○							
44	112.05	110.67	120														○	○	○	○	○	○	○	○	○	○					
48	122.23	120.86	129																○	○	○	○	○	○	○	○					
50	127.32	125.95	136																	○	○	○	○	○	○	○					
60	152.79	151.42	160																		○	○	○	○	○	○					

□ : AF-S 형 ○ : AF-S · AF-F 형

S14M0400 (벨트폭 40mm용) W=52mm

폴리				축경 d/D1/L[mm]														
잇수	dp	do	Fo	축경 d	28	30	32	35	38	40	42	45	48	50	55	60	65	
				D1	54	54	59	59	64	64	74	74	79	79	84	89	94	
				L	70	70	70	70	70	70	76	76	76	76	76	76	76	
				전달 토크 (N·m)	365	390	415	455	495	520	990	1060	1130	1180	1300	1410	1530	
28	124.78	121.98	136	클램프 나사수 (축경) ϕ28~40 4-M6 (축경) ϕ42~65 4-M8	○	○	○	○	○	○	○	○	○	○	○	○	○	
30	133.69	130.90	145			○	○	○	○	○	○	○	○	○	○	○	○	
32	142.60	139.81	154				○	○	○	○	○	○	○	○	○	○	○	
34	151.52	148.72	163							○	○	○	○	○	○	○	○	
36	160.43	157.63	172							○	○	○	○	○	○	○	○	
40	178.25	175.46	189							○	○	○	○	○	○	○	○	
42	187.17	184.37	198							○	○	○	○	○	○	○	○	
44	196.08	193.28	207							○	○	○	○	○	○	○	○	
48	213.90	211.11	225							○	○	○	○	○	○	○	○	○
50	222.82	220.02	234							○	○	○	○	○	○	○	○	○

○ : AF-S · AF-F 형

S14M0600 (벨트폭 60mm용) W=73mm

폴리				축경 d/D1/L [mm]							
잇수	dp	do	Fo	축경 d	35	38	40	42	45	48	50
				D1	59	64	64	74	74	79	79
				L	91	91	91	97	97	97	97
				전달 토크 (N·m)	455	495	520	990	1060	1130	1180
28	124.78	121.98	136	클램프 나사수 (축경) ϕ 28~40 4-M6 (축경) ϕ 42~65 4-M8	○	○	○	○	○	○	○
30	133.69	130.90	145		○	○	○	○	○	○	○
32	142.60	139.81	154		○	○	○	○	○	○	○
34	151.52	148.72	163				○	○	○	○	○
36	160.43	157.63	172				○	○	○	○	○
40	178.25	175.46	189					○	○	○	○
42	187.17	184.37	198					○	○	○	○
44	196.08	193.28	207					○	○	○	○
48	213.90	211.11	225					○	○	○	○
50	222.82	220.02	234					○	○	○	○

○ : AF-S · AF-F 형