




폴리우레탄 양면 싱크로 벨트 표준길이

DXL형					
					
벨트 표준폭					
호칭폭	025	031	037	050	175
폭 (mm)	6.4	7.9	9.5	12.7	19.1
B E L T S I Z E					
호 칭	피치원주 (mm)	잇수	R	u	
140DXL	355.60	70	-	●	
146DXL	370.84	73	-	●	
150DXL	381.00	75	-	●	
166DXL	421.64	83	-	●	
170DXL	431.80	85	-	●	
180DXL	457.20	90	-	●	
190DXL	482.60	95	-	●	
200DXL	508.00	100	-	●	
210DXL	533.40	105	-	●	
220DXL	558.80	110	-	●	
230DXL	584.20	115	-	●	
240DXL	609.60	120	-	●	
270DXL	685.80	135	-	●	
290DXL	736.60	145	-	●	
300DXL	762.00	150	-	●	
320DXL	812.80	160	-	●	
376DXL	955.04	188	-	●	
400DXL	1016.00	200	-	●	
430DXL	1092.20	215	-	●	
490DXL	1244.60	245	-	●	

DT5형					
					
벨트 표준폭					
호칭폭	5	10	15	20	25
폭 (mm)	5	10	15	20	25
B E L T S I Z E					
호 칭	피치원주 (mm)	잇수	R	u	
DT5- 300	300.0	60	-	●	
DT5- 410	410.0	82	-	●	
DT5- 460	460.0	92	-	●	
DT5- 480	480.0	96	-	●	
DT5- 515	515.0	103	-	●	
DT5- 550	550.0	110	-	●	
DT5- 590	590.0	118	-	●	
DT5- 620	620.0	124	-	●	
DT5- 650	650.0	130	-	●	
DT5- 700	700.0	140	-	●	
DT5- 750	750.0	150	-	●	
DT5- 800	800.0	160	-	●	
DT5- 815	815.0	163	-	●	
DT5- 860	860.0	172	-	●	
DT5- 900	900.0	180	-	●	
DT5- 940	940.0	188	-	●	
DT5-1075	1075.0	215	-	●	
DT5-1100	1100.0	220	-	●	

DT10형					
					
벨트 표준폭					
호칭폭	15	20	25	30	50
폭 (mm)	15	20	25	30	50
B E L T S I Z E					
호 칭	피치원주 (mm)	잇수	R	u	
DT10- 260	260.0	26	-	●	
DT10- 530	530.0	53	-	●	
DT10- 630	630.0	63	-	●	
DT10- 660	660.0	66	-	●	
DT10- 700	700.0	70	-	●	
DT10- 720	720.0	72	-	●	
DT10- 800	800.0	80	-	●	
DT10- 840	840.0	84	-	●	
DT10- 900	900.0	90	-	●	
DT10- 980	980.0	98	-	●	
DT10-1100	1100.0	110	-	●	
DT10-1210	1210.0	121	-	●	
DT10-1240	1240.0	124	-	●	
DT10-1250	1250.0	125	-	●	
DT10-1320	1320.0	132	-	●	
DT10-1350	1350.0	135	-	●	
DT10-1420	1420.0	142	-	●	
DT10-1500	1500.0	150	-	●	
DT10-1610	1610.0	161	-	●	
DT10-1800	1800.0	180	-	●	
DT10-1880	1880.0	188	-	●	

주) 벨트 길이, 벨트 폭 허용차는 (S-88 페이지)를 참조 하십시오.