

TN10형 기준전동용량표 (6mm폭당)

단위 : W

소PULLEY잇수		16	18	20	22	24	26	28	30	32
피치원직경 (mm)		5.09	5.73	6.37	7.00	7.64	8.28	8.91	9.55	10.19
소 폴 리 회 전 수 (rpm)	950	1.4	1.6	1.8	1.9	2.1	2.3	2.5	2.7	2.8
	1160	1.7	1.9	2.2	2.4	2.6	2.8	3.0	3.2	3.5
	1425	2.1	2.4	2.7	2.9	3.2	3.5	3.7	4.0	4.2
	1750	2.6	2.9	3.3	3.6	3.9	4.2	4.6	4.9	5.2
	2850	4.2	4.8	5.3	5.8	6.4	6.9	7.4	8.0	8.5
	3450		5.8	6.4	7.1	7.7	8.3	9.0	9.6	10.3
	100	0.1	0.2	0.2	0.2	0.2	0.2	0.3	0.3	0.3
	200	0.3	0.3	0.4	0.4	0.4	0.5	0.5	0.6	0.6
	300	0.4	0.5	0.6	0.6	0.7	0.7	0.8	0.8	0.9
	400	0.6	0.7	0.7	0.8	0.9	1.0	1.0	1.1	1.2
	500	0.7	0.8	0.9	1.0	2.1	1.2	1.3	1.4	1.5
	600	0.9	1.0	1.1	1.2	1.3	1.5	1.6	1.7	1.8
	700	1.0	1.2	1.3	1.4	1.6	1.7	1.8	2.0	2.1
	800	1.2	1.3	1.5	1.6	1.8	1.9	2.1	2.2	2.4
	900	1.3	1.5	1.7	1.8	2.0	2.2	2.3	2.5	2.7
	1000	1.5	1.7	1.9	2.0	2.2	2.4	2.6	2.8	3.0
	1100	1.6	1.8	2.0	2.3	2.5	2.7	2.9	3.1	3.3
	1200	1.8	2.0	2.2	2.5	2.7	2.9	3.1	3.4	3.6
	1300	1.9	2.2	2.4	2.1	2.9	3.1	3.4	3.6	3.9
	1400	2.1	2.3	2.6	2.9	3.1	3.4	3.7	3.9	4.2
	1500	2.2	2.5	2.8	3.1	3.4	3.6	3.9	4.2	4.5
	1600	2.4	2.7	3.0	3.3	3.6	3.9	4.2	4.5	4.8
	1700	2.5	2.9	3.2	3.5	3.8	4.1	4.4	4.7	5.1
	1800	2.7	3.0	3.4	3.7	4.0	4.4	4.7	5.0	5.4
	1900	2.8	3.2	3.5	3.9	4.2	4.6	5.0	5.3	5.7
	2000	3.0	3.4	3.7	4.1	4.5	4.8	5.2	5.6	6.0
	2100	3.1	3.5	3.9	4.3	4.7	5.1	5.5	5.9	6.3
	2200	3.3	3.7	4.1	4.5	4.9	5.3	5.7	6.1	6.6
	2300	3.4	3.9	4.3	4.7	5.1	5.6	6.0	6.4	6.8
	2400	3.6	4.0	4.5	4.9	5.4	5.8	6.3	6.7	7.1
	2500	3.7	4.2	4.7	5.1	5.6	6.0	6.5	7.0	7.4
	2600	3.9	4.4	4.8	5.3	5.8	6.3	6.8	7.3	7.7
	2700	4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0
	2800	4.2	4.7	5.2	5.7	6.3	6.8	7.3	7.8	8.3
	2900	4.3	4.9	5.4	5.9	6.5	7.0	7.6	8.1	8.6
	3000	4.5	5.0	5.6	6.1	6.7	7.3	7.8	8.4	8.9
	3200		5.4	6.0	6.6	7.1	7.7	8.3	8.9	9.5
	3400		5.7	6.3	7.0	7.6	8.2	8.9	9.5	10.1
	3600		6.0	6.7	7.4	8.0	8.7	9.4	10.0	10.7
	3800		6.4	7.1	7.8	8.5	9.2	9.9	10.6	11.3
	4000		6.7	7.4	8.2	8.9	9.7	10.4	11.1	11.9
	4200		7.0	7.8	8.6	9.4	10.1	10.9	11.7	12.5
	4400		7.4	8.2	9.0	9.8	10.6	11.4	12.2	13.1
	4600		7.7	8.6	9.4	10.3	11.1	12.0	12.8	13.6
	4800		8.0	8.9	9.8	10.7	11.6	12.5	13.3	14.2
	5000		8.4	9.3	10.2	11.1	12.1	13.0	13.9	14.8
	5500		9.2	10.2	11.2	12.2	13.3	14.3	15.3	16.3
	6000		10.0	11.1	12.2	13.3	14.4	15.5	16.6	17.7

표시범위에서의 사용은 벨트수명이 단축됩니다.