

TN15형 기준전동용량표 (10mm폭당)

단위 : W

소PULLEY잇수		20	22	24	26	28	30	32	34	36	40	44
피치원직경 (mm)		9.55	10.50	11.46	12.41	13.37	14.32	15.28	16.23	17.19	19.10	21.01
소 풀 리 회 전 수 (rpm)	950	10.2	11.3	12.3	13.3	14.3	15.4	16.4	17.4	18.4	20.5	22.5
	1160	12.5	13.8	15.0	16.3	17.5	18.8	20.0	21.3	22.5	25.0	27.5
	1425	15.4	16.9	18.4	20.0	21.5	23.0	24.6	26.1	27.6	30.7	33.8
	1750	18.9	20.8	22.6	24.5	26.4	28.3	30.2	32.1	33.9	37.7	41.5
	2850	30.7	33.8	36.8	39.9	43.0	46.0	49.1	52.1	55.2	61.3	67.3
	3450		40.9	44.6	48.3	52.0	55.7	59.3	63.0	66.7	74.0	81.3
	100	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.2	2.4
	200	2.2	2.4	2.6	2.8	3.0	3.2	3.5	3.7	3.9	4.3	4.7
	300	3.2	3.6	3.9	4.2	4.5	4.9	5.2	5.5	5.8	6.5	7.1
	400	4.3	4.7	5.2	5.6	6.0	6.5	6.9	7.3	7.8	8.6	9.5
	500	5.4	5.9	6.5	7.0	7.6	8.1	8.6	9.2	9.7	10.8	11.9
	600	6.5	7.1	7.8	8.4	9.1	9.7	10.4	11.0	11.6	12.9	14.2
	700	7.6	8.3	9.1	9.8	10.6	11.3	12.1	12.8	13.6	15.1	16.6
	800	8.6	9.5	10.4	11.2	12.1	12.9	13.8	14.7	15.5	17.3	19.0
	900	9.7	10.7	11.6	12.6	13.6	14.6	15.5	16.5	17.5	19.4	21.4
	1000	10.8	11.9	12.9	14.0	15.1	16.2	17.3	18.3	19.4	21.6	23.7
	1100	11.9	13.1	14.2	15.4	16.6	17.8	19.0	20.2	21.4	23.7	26.1
	1200	12.9	14.2	15.5	16.8	18.1	19.4	20.7	22.0	23.3	25.9	28.5
	1300	14.0	15.4	16.8	18.2	19.6	21.0	22.4	23.8	25.2	28.0	30.8
	1400	15.1	16.6	18.1	19.6	21.1	22.6	24.2	25.7	27.2	30.2	33.2
	1500	16.2	17.8	19.4	21.0	22.6	24.3	25.9	27.5	29.1	32.3	35.6
	1600	17.3	19.0	20.7	22.4	24.2	25.9	27.6	29.3	31.0	34.5	37.9
	1700	18.3	20.2	22.0	23.8	25.7	27.5	29.3	31.1	33.0	36.6	40.3
	1800	19.4	21.4	23.3	25.2	27.2	29.1	31.0	33.0	34.9	38.8	42.6
	1900	20.5	22.5	24.6	26.6	28.7	30.7	32.8	34.8	36.8	40.9	45.0
	2000	21.6	23.7	25.9	28.0	30.2	32.3	34.5	36.6	38.8	43.1	47.4
	2100	22.6	24.9	27.2	29.4	31.7	33.9	36.2	38.5	40.7	45.2	49.7
	2200	23.7	26.1	28.5	30.8	33.2	35.6	37.9	40.3	42.6	47.4	52.1
	2300	24.8	27.3	29.7	32.2	34.7	37.2	39.6	42.1	44.6	49.5	54.4
	2400	25.9	28.5	31.0	33.6	36.2	38.8	41.4	43.9	46.5	51.6	56.8
	2500	27.0	29.6	32.3	35.0	37.7	40.4	43.1	45.8	48.4	53.8	59.1
	2600	28.0	30.8	33.6	36.4	39.2	42.0	44.8	47.6	50.4	55.9	61.5
	2700	29.1	32.0	34.9	37.8	40.7	43.6	46.5	49.4	52.3	58.1	63.8
	2800	30.2	33.2	36.2	39.2	42.2	45.2	48.2	51.2	54.2	60.2	66.2
	2900	31.3	34.4	37.5	40.6	43.7	46.8	49.9	53.0	56.1	62.3	68.5
	3000	32.3	35.6	38.8	42.0	45.2	48.4	51.6	54.9	58.1	64.5	70.8
	3200		37.9	41.4	44.8	48.2	51.6	55.1	58.5	61.9	68.7	75.5
	3400		40.3	43.9	47.6	51.2	54.9	58.5	62.1	65.7	73.0	80.2
	3600		42.6	46.5	50.4	54.2	58.1	61.9	65.7	69.6	77.2	84.8
	3800		45.0	49.1	53.1	57.2	61.3	65.3	69.4	73.4	81.4	89.5
	4000		47.4	51.6	55.9	60.2	64.5	68.7	73.0	77.2	85.7	94.1
	4200		49.7	54.2	58.7	63.2	67.7	72.1	76.6	81.0	89.9	98.7
	4400		52.1	56.8	61.5	66.2	70.8	75.5	80.2	84.8	94.1	103.3
	4600		54.4	59.3	64.2	69.1	74.0	78.9	83.8	88.6	98.3	107.9
	4800		56.8	61.9	67.0	72.1	77.2	82.3	87.3	92.4	102.5	112.4
	5000		59.1	64.5	69.8	75.1	80.4	85.7	90.9	96.2	106.6	117.0
	5500		65.0	70.8	76.7	82.5	88.3	94.1	99.8	105.6	117.0	128.3
	6000		70.8	77.2	83.6	89.9	96.2	102.5	108.7	114.9	127.3	139.5

표시범위 내에서 사용은 벨트수명이 단축됩니다.

주) TN15타입 폴리에스테르 코드의 벨트 기준전동용량은 상기표와 상이합니다.
설계시에는 별도 문의 바랍니다.