

TN15형 기준전동용량표 (10mm폭당)

단위 : W

소PULLEY잇수		48	52	56	60	64	68	72	80	88	96
피치원직경 (mm)		22.92	24.83	26.74	28.65	30.56	32.47	34.38	38.20	42.02	45.84
소 폴 리 회 전 수 (rpm)	950	24.6	26.6	28.7	30.7	32.8	34.8	36.8	40.9	45.0	49.1
	1160	30.0	32.5	35.0	27.5	40.0	42.5	45.0	49.9	54.9	59.9
	1425	36.8	39.9	43.0	46.0	49.1	52.1	55.2	61.3	67.3	73.4
	1750	45.2	49.0	52.7	56.5	60.2	63.9	67.7	75.1	82.5	89.9
	2850	73.4	79.4	85.5	91.5	97.4	103.4	109.3	121.1	132.8	144.4
	3450	88.6	95.9	103.1	110.3	117.4	124.5	131.6	145.6	159.4	173.0
	100	2.6	2.8	3.0	3.2	3.5	3.7	3.9	4.3	4.7	5.2
	200	5.2	5.6	6.0	6.5	6.9	7.3	7.8	8.6	9.5	10.4
	300	7.8	8.4	9.1	9.7	10.4	11.0	11.6	12.9	14.2	15.5
	400	10.4	11.2	12.1	12.9	13.8	14.7	15.5	17.3	19.0	20.7
	500	12.9	14.0	15.1	16.2	17.3	18.3	19.4	21.6	23.7	25.9
	600	15.5	16.8	18.1	19.4	20.7	22.0	23.3	25.9	28.5	31.0
	700	18.1	19.6	21.1	22.6	24.2	25.7	27.2	30.2	33.2	36.2
	800	20.7	22.4	24.2	25.9	27.6	29.3	31.0	34.5	37.9	41.4
	900	23.3	25.2	27.2	29.1	31.0	33.0	34.9	38.8	42.6	46.5
	1000	25.9	28.0	30.2	32.3	34.5	36.6	38.8	43.1	47.4	51.6
	1100	28.5	30.8	33.2	35.6	37.9	40.3	42.6	47.4	52.1	56.8
	1200	31.0	33.6	36.2	38.8	41.4	43.9	46.5	51.6	56.8	61.9
	1300	33.6	36.4	39.2	42.0	44.8	47.6	50.4	55.9	61.5	67.0
	1400	36.2	39.2	42.2	45.2	48.2	51.2	54.2	60.2	66.2	72.1
	1500	38.8	42.0	45.2	48.4	51.6	54.9	58.1	64.5	70.8	77.2
	1600	41.4	44.8	48.2	51.6	55.1	58.5	61.9	68.7	75.5	82.3
	1700	43.9	47.6	51.2	54.9	58.5	62.1	65.7	73.0	80.2	87.3
	1800	46.5	50.4	54.2	58.1	61.9	65.7	69.6	77.2	84.8	92.4
	1900	49.1	53.1	57.2	61.3	65.3	69.4	73.4	81.4	89.5	97.4
	2000	51.6	55.9	60.2	64.5	68.7	73.0	77.2	85.7	94.1	102.5
	2100	54.2	58.7	63.2	67.7	72.1	76.6	81.0	89.9	98.7	107.5
	2200	56.8	61.5	66.2	70.8	75.5	80.2	84.8	94.1	103.3	112.4
	2300	59.3	64.2	69.1	74.0	78.9	83.8	88.6	98.3	107.9	117.4
	2400	61.9	67.0	72.1	77.2	82.3	87.3	92.4	102.5	112.4	122.4
	2500	64.5	69.8	75.1	80.4	85.7	90.9	96.2	106.6	117.0	127.3
	2600	67.0	72.5	78.1	83.6	89.0	94.5	99.9	11.08	121.5	132.2
	2700	69.6	75.3	81.0	86.7	92.4	98.1	103.7	114.9	126.1	137.1
	2800	72.1	78.1	84.0	89.9	95.8	101.6	107.5	119.1	130.6	142.0
	2900	74.7	80.8	86.9	93.0	99.1	105.2	111.2	123.2	135.1	146.8
	3000	77.2	83.6	89.9	96.2	102.5	108.7	114.9	127.3	139.5	151.6
	3200	82.3	89.0	95.8	102.5	109.1	115.8	122.4	135.5	148.4	161.2
	3400	87.3	94.5	101.6	108.7	115.8	122.8	129.7	143.6	157.2	170.6
	3600	92.4	99.9	107.5	114.9	122.4	129.7	137.1	151.6	165.9	180.0
	3800	97.4	105.4	113.3	121.1	128.9	136.7	144.4	159.6	174.5	189.2
	4000	102.5	110.8	119.1	127.3	135.5	143.6	151.6	167.5	183.0	198.3
	4200	107.5	116.2	124.8	133.4	142.0	150.4	158.8	175.3	191.5	207.2
	4400	112.4	121.5	130.6	139.5	148.4	157.2	165.9	183.0	199.8	216.1
	4600	117.4	126.9	136.3	145.6	154.8	163.9	173.0	190.7	208.0	224.1
	4800	122.4	132.2	142.0	151.6	161.2	170.6	180.0	198.3	216.1	233.3
	5000	127.3	137.5	147.6	157.6	167.5	177.2	186.9	205.7	224.0	241.6
	5500	139.5	150.6	161.6	172.4	183.0	193.6	203.9	224.0	243.3	261.8
	6000	151.6	163.5	175.3	186.9	198.3	209.5	220.4	241.6	261.8	280.8

주) TN15타입 폴리에스테르 코드의 벨트 기준전동용량은 상기표와 상이합니다.  
설계시에는 별도 문의 바랍니다.