



TL 싱크로 폴리 표준 치수표 (부싱 타입)


4-2A 형




4-2B 형




5-1F 형



5-1 형



5-2 형



H200 (벨트폭 50.8mm용)

는 재고판매 하고 있습니다.

단위 : mm

잇수	dp	do	형상	PULLEY 재질	TL BUSH		W	WA	S	db	l	S ₁	S ₂	S ₃	H	PULLEY 예상질량 (kg)	플랜지 품번
					형번	최대축홀											
24	97.02	95.65	4-1BF	기탄 계소 구강 조강 용재	6340	42	59	54	2.5	-	40	-	19	-	-	1.9	F 10385
25	101.06	99.69	4-1BF		6340	42	59	54	2.5	-	40	-	19	-	-	2.2	F 11190
26	105.11	103.73	4-1BF		6340	42	59	54	2.5	-	40	-	19	-	-	2.5	F 11190
28	113.19	111.82	4-1BF		6340	42	59	54	2.5	-	40	-	19	-	-	3.1	F119100
30	121.28	119.90	4-1BF		6340	42	59	54	2.5	-	40	-	19	-	-	3.5	F127105
32	129.36	127.99	5-1F	회 주 철	6340	42	59	54	2.5	-	40	-	10	9	13	3.6	F135115
34	137.45	136.07	5-1F		6340	42	59	54	2.5	-	40	-	10	9	13	4.1	F144125
36	145.53	144.16	5-1F		6340	42	59	54	2.5	-	40	-	10	9	13	4.7	F152130
40	161.70	160.33	5-1		8545	60	59	-	-	-	45	-	10	4	13	5.3	-
42	169.79	168.41	5-1		8545	60	59	-	-	-	45	-	10	4	13	6.0	-
44	177.87	176.50	5-1		8545	60	59	-	-	-	45	-	10	4	13	6.8	-
48	194.04	192.67	5-1		8545	60	59	-	-	-	45	-	10	4	13	8.4	-
50	202.13	200.76	5-2		8545	60	59	-	-	125	45	-	10	4	13	6.7	-
60	242.55	241.18	5-2		8545	60	59	-	-	140	45	-	10	4	13	8.4	-
72	291.06	289.69	5-2		8545	60	59	-	-	140	45	-	10	4	13	9.6	-
84	339.57	338.20	5-2		8545	60	59	-	-	140	45	-	10	4	13	11.3	-
96	388.08	386.71	4-2A		11055	75	59	-	-	180	55	-	-	4	13	16.8	-

H300 (벨트폭 76.2mm용)

는 재고판매 하고 있습니다.

단위 : mm

잇수	dp	do	형상	PULLEY 재질	TL BUSH		W	WA	S	db	l	S ₁	S ₂	S ₃	H	PULLEY 예상질량 (kg)	플랜지 품번
					형번	최대축홀											
40	161.70	160.33	5-1	회 주 철	8545	60	85	-	-	-	45	-	25	15	14	6.5	-
42	169.79	168.41	5-1		8545	60	85	-	-	-	45	-	25	15	14	7.3	-
44	177.87	176.50	5-1		8545	60	85	-	-	-	45	-	25	15	14	8.1	-
48	194.04	192.67	5-1		8545	60	85	-	-	-	45	-	25	15	14	9.8	-
50	202.13	200.76	5-1		8545	60	85	-	-	-	45	-	25	15	14	10.7	-
60	242.55	241.18	5-2		8545	60	85	-	-	140	45	-	25	15	14	10.6	-
72	291.06	289.69	5-2		11055	75	85	-	-	180	55	-	15	15	14	15.9	-