

KPSⅡ 14M 형 기준 전동용량표 (40mm폭 : 1400mm당)

단위 : kW

작은 풀리 잇 수		42	44	48	50	60	64	72	84	96	120	144
피치원직경 (mm)		187.17	196.08	213.90	222.82	267.38	285.21	320.86	374.33	427.81	534.76	641.71
소 풀 리 회 전 수 (m p r)	575	31.36	32.85	35.83	37.31	44.73	47.69	53.61	62.44	71.23	88.64	105.79
	695	37.13	38.89	42.40	44.16	52.92	56.41	63.37	73.76	84.06	104.38	124.23
	725	38.55	40.37	44.02	45.84	54.93	58.55	65.77	76.53	87.20	108.21	128.69
	870	45.30	47.44	51.72	53.85	64.47	68.70	77.12	89.62	101.97	126.10	149.31
	950	48.95	51.26	55.87	58.17	69.62	74.17	83.22	96.64	109.85	135.53	
	1160	58.33	61.06	66.52	69.24	82.75	88.10	98.70	114.33	129.59		
	1425	69.73	72.98	79.44	82.66	98.55	104.82	117.16	135.17			
	1750	83.14	86.96	94.55	98.31	116.79	124.01	138.11				
	2850	123.88	129.20									
	3450											
	100	6.46	6.77	7.38	7.69	9.23	9.85	11.08	12.92	14.77	18.46	22.14
	150	9.34	9.79	10.68	11.12	13.35	14.24	16.02	18.68	21.35	26.68	32.01
	200	12.13	12.71	13.86	14.44	17.33	18.48	20.79	24.25	27.71	34.62	41.51
	250	14.84	15.55	16.96	17.67	21.20	22.61	25.43	29.66	33.89	42.33	50.74
	300	17.50	18.33	19.99	20.82	24.98	26.65	29.97	34.95	39.93	49.85	59.74
	350	20.10	21.06	22.97	23.92	28.70	30.61	34.42	40.14	45.84	57.21	68.52
	400	22.66	23.74	25.90	26.97	32.35	34.50	38.80	45.23	51.65	64.43	77.12
	450	25.19	26.39	28.78	29.97	35.95	38.34	43.11	50.24	57.36	71.51	85.53
	500	27.68	29.00	31.62	32.94	39.50	42.12	47.35	55.17	62.97	78.45	93.76
	600	32.57	34.12	37.21	38.75	46.46	49.53	55.66	64.83	73.94	91.98	109.71
	700	37.36	39.14	42.67	44.44	53.25	56.77	63.77	74.22	84.59	105.02	124.98
	800	42.06	44.05	48.03	50.01	59.90	63.84	71.69	83.36	94.92	117.59	139.54
	900	46.68	48.88	53.28	55.48	66.41	70.76	79.42	92.27	104.95	129.67	
	1000	51.21	53.63	58.44	60.85	72.80	77.54	86.97	100.94	114.67	141.26	
	1100	55.68	58.30	63.52	66.12	79.05	84.18	94.36	109.38	124.09		
	1200	60.08	62.89	68.51	71.31	85.19	90.68	101.57	117.59	133.19		
	1300	64.41	67.42	73.42	76.41	91.20	97.05	108.61	125.55	141.97		
	1400	68.68	71.88	78.25	81.42	97.10	103.28	115.47	133.28			
	1500	72.88	76.27	83.00	86.35	102.88	109.38	122.16	140.75			
	1600	77.03	80.59	87.68	91.20	108.53	115.33	128.68				
	1700	81.11	84.85	92.28	95.96	114.07	121.15	135.01				
	1800	85.14	89.05	96.80	100.64	119.49	126.83					
	1900	89.11	93.18	101.25	105.24	124.78	132.37					
	2000	93.02	97.25	105.62	109.76	129.95	137.76					
	2200	100.67	105.19	114.13	118.54							
	2400	108.08	112.88	122.32	126.97							
	2600	115.26	120.30	130.20								
	2800	122.19	127.45									
	3000	128.87										
	3200											
	3400											
	3600											
	3800											
	4000											