

● Ceptor-VI S8M형

기준전동용량 (60mm폭: 길이1200mm당)

단위 : kW

작은폴리잇수		22	24	26	28	30	32	34	36	40	44	48	50	60	72	84	96	120
피치원직경 (mm)		56.02	61.12	66.21	71.30	76.39	81.49	86.58	91.67	101.86	112.05	122.23	127.32	152.79	183.35	213.9	244.46	305.58
소 폴리 회 전 수 (m p r)	575	9.4	10.8	12.4	14.1	15.8	17.4	19.1	20.9	24.0	27.4	30.6	32.0	38.9	46.3	53.1	59.8	73.0
	690	11.1	12.8	14.6	16.6	18.6	20.5	22.5	24.6	28.3	32.2	36.0	37.7	45.8	54.4	62.4	70.3	85.7
	725	11.6	13.4	15.3	17.3	19.5	21.5	23.5	25.7	29.6	33.7	37.6	39.4	47.9	56.9	65.2	73.5	89.5
	870	13.6	15.7	18.0	20.4	22.9	25.3	27.7	30.2	34.8	39.6	44.2	46.4	56.3	66.8	76.7	86.3	105.1
	950	14.7	17.0	19.5	22.1	24.8	27.3	29.9	32.7	37.6	42.9	47.8	50.1	60.8	72.2	82.8	93.2	113.5
	1160	17.6	20.4	23.3	26.3	29.6	32.6	35.8	39.0	44.9	51.1	57.1	59.8	72.5	86.1	98.7	111.0	135.1
	1425	21.2	24.4	27.9	31.6	35.5	39.1	42.9	46.8	53.8	61.2	68.3	71.6	86.8	103.0	117.9	132.6	161.3
	1750	25.3	29.2	33.4	37.8	42.5	46.8	51.3	55.9	64.3	73.2	81.6	85.5	103.6	122.9	140.7	158.1	192.1
	2850	38.3	44.2	50.5	57.1	64.1	70.6	77.3	84.3	96.9	110.1	122.7	128.5	155.4	184.0	210.3	236.0	286.0
	3450	44.7	51.6	58.8	66.5	74.7	82.2	90.0	98.1	112.7	128.0	142.6	149.3	180.3	213.2	243.5	273.1	330.4
	50	1.0	1.2	1.3	1.5	1.7	1.9	2.1	2.3	2.6	3.0	3.3	3.5	4.2	5.1	5.8	6.6	8.1
	100	1.9	2.2	2.5	2.9	3.2	3.5	3.9	4.3	4.9	5.6	6.3	6.6	8.0	9.5	11.0	12.4	15.2
	200	3.6	4.2	4.8	5.4	6.1	6.7	7.3	8.0	9.2	10.5	11.8	12.4	15.0	17.9	20.6	23.2	28.4
	300	5.2	6.0	6.9	7.8	8.8	9.7	10.6	11.6	13.4	15.2	17.0	17.8	21.7	25.8	29.7	33.5	40.9
	400	6.8	7.8	8.9	10.1	11.4	12.6	13.8	15.0	17.3	19.7	22.1	23.1	28.1	33.4	38.4	43.3	52.8
	500	8.3	9.6	10.9	12.4	13.9	15.4	16.8	18.4	21.2	24.1	27.0	28.3	34.3	40.8	46.9	52.8	64.5
	600	9.8	11.3	12.9	14.6	16.4	18.1	19.8	21.7	25.0	28.4	31.8	33.3	40.4	48.1	55.2	62.1	75.8
	700	11.2	13.0	14.8	16.8	18.9	20.8	22.8	24.9	28.7	32.6	36.4	38.2	46.4	55.1	63.2	71.2	86.8
	800	12.6	14.6	16.7	18.9	21.3	23.4	25.7	28.0	32.3	36.8	41.1	43.0	52.2	62.1	71.2	80.1	97.6
	900	14.1	16.2	18.6	21.0	23.6	26.0	28.5	31.2	35.9	40.8	45.6	47.8	58.0	68.9	79.0	88.9	108.3
	1000	15.4	17.8	20.4	23.1	25.9	28.6	31.3	34.2	39.4	44.8	50.0	52.5	63.6	75.6	86.6	97.5	118.7
	1100	16.8	19.4	22.2	25.1	28.2	31.1	34.1	37.2	42.9	48.8	54.4	57.1	69.2	82.2	94.2	106.0	129.0
	1200	18.2	21.0	24.0	27.1	30.5	33.6	36.8	40.2	46.3	52.7	58.8	61.6	74.7	88.7	101.6	114.3	139.1
	1300	19.5	22.5	25.7	29.1	32.7	36.1	39.5	43.2	49.7	56.5	63.1	66.1	80.1	95.1	108.9	122.5	149.1
1400	20.8	24.0	27.5	31.1	34.9	38.5	42.2	46.1	53.0	60.3	67.3	70.5	85.4	101.4	116.2	130.6	158.9	
1500	22.1	25.5	29.2	33.0	37.1	40.9	44.8	48.9	56.3	64.0	71.4	74.9	90.7	107.6	123.3	138.6	168.5	
1600	23.4	27.0	30.9	35.0	39.3	43.3	47.4	51.8	59.5	67.7	75.6	79.2	95.9	113.8	130.3	146.5	178.1	
1700	24.7	28.5	32.6	36.9	41.4	45.6	50.0	54.5	62.7	71.4	79.6	83.4	101.1	119.9	137.2	154.3	187.4	
1800	26.0	30.0	34.2	38.7	43.5	47.9	52.5	57.3	65.9	75.0	83.6	87.6	106.1	125.8	144.1	161.9	196.7	
1900	27.2	31.4	35.9	40.6	45.6	50.2	55.0	60.0	69.1	78.5	87.6	91.8	111.1	131.7	150.8	169.5	205.8	
2000	28.4	32.8	37.5	42.4	47.6	52.5	57.5	62.7	72.1	82.1	91.5	95.9	116.1	137.6	157.4	176.9	214.8	
2200	30.9	35.6	40.7	46.0	51.7	56.9	62.4	68.0	78.2	89.0	99.2	103.9	125.7	149.0	170.5	191.5	232.4	
2400	33.2	38.3	43.8	49.5	55.6	61.2	67.1	73.2	84.1	95.7	106.7	111.7	135.2	160.1	183.1	205.7	249.5	
2600	35.5	41.0	46.8	53.0	59.5	65.5	71.7	78.2	89.9	102.2	113.9	119.3	144.3	170.9	195.4	219.4	266.0	
2800	37.8	43.6	49.8	56.3	63.2	69.6	76.2	83.1	95.5	108.6	121.0	126.7	153.2	181.4	207.4	232.7	282.1	
3000	40.0	46.1	52.6	59.6	66.8	73.6	80.6	87.9	101.0	114.8	127.9	133.9	161.9	191.6	218.9	245.6	297.6	
3200	42.1	48.6	55.4	62.7	70.4	77.5	84.9	92.5	106.3	120.8	134.6	140.9	170.3	201.4	230.1	258.1	312.5	
3400	44.2	51.0	58.2	65.8	73.8	81.2	89.0	97.0	111.4	126.6	141.0	147.6	178.4	210.9	240.9	270.1		
3600	46.2	53.3	60.8	68.8	77.2	84.9	93.0	101.3	116.4	132.2	147.2	154.2	186.2	220.1	251.3	281.7		
3800	48.2	55.5	63.3	71.6	80.4	88.4	96.8	105.5	121.2	137.6	153.3	160.5	193.7	228.9	261.2	292.8		
4000	50.1	57.7	65.8	74.4	83.5	91.8	100.5	109.6	125.8	142.9	159.1	166.5	200.9	237.3	270.8			
4500	54.5	62.8	71.6	80.9	90.7	99.8	109.2	119.0	136.6	155.0	172.5	180.5	217.6	256.8	292.8			
5000	58.5	67.3	76.7	86.7	97.2	106.9	117.0	127.4	146.1	165.7	184.4	192.9	232.3	273.8				
5500	62.0	71.3	81.3	91.8	102.9	113.1	123.7	134.7	154.3	175.0	194.5	203.5	244.8					
6000	64.9	74.7	85.1	96.1	107.6	118.3	129.3	140.8	161.2	182.7	202.9	212.2	255.0					

범위안에서의 사용은 벨트 스피드가 33m/s이상 이 되므로 폴리의 움직임 발란스를 확인하여 사용해 주시기 바랍니다.

Ceptor-VI S8M 폭보정계수표 (Kb)

벨트폭(mm)	25	40	60	80	100	150
폭보정계수	0.37	0.63	1.00	1.39	1.79	2.84