

S3M · DS3M형 허용장력표 (6mm폭당)

단위 : N

소 폴 리 잇 수	14	15	16	18	20	22	24	26	28	30	
피치원직경 (mm)	13.37	14.32	15.28	17.19	19.10	21.01	22.92	24.83	26.74	28.65	
소 폴 리 회 전 수 (m p r)	725	90	92	93	94	94	94	94	93	93	
	870	87	89	90	91	91	91	90	90	89	
	950	86	87	88	89	90	90	89	89	88	
	1160	82	83	84	86	86	86	86	85	85	
	1425	78	80	81	82	82	82	82	82	81	
	1750	75	76	77	78	79	79	79	78	78	
	2850	66	68	69	70	70	70	70	69	69	
	3450	63	64	65	66	67	67	67	66	66	
	50	138	139	140	141	142	142	141	141	140	
	100	125	127	128	129	129	129	129	129	128	
	200	113	115	115	117	117	117	117	116	116	
	300	106	107	108	109	110	110	110	109	109	
	400	101	102	103	104	105	105	105	104	104	
	500	97	98	99	100	101	101	101	100	100	
	600	94	95	96	97	98	98	97	97	97	
	700	93	92	93	94	95	95	95	94	94	
	800	89	90	91	92	93	93	92	92	91	
	900	87	88	89	90	90	91	90	90	89	
	1000	85	86	87	88	89	89	88	88	87	
	1100	83	84	85	87	87	87	97	86	86	
	1200	82	83	84	85	85	85	85	85	84	
	1300	80	81	82	84	84	84	84	83	83	
	1400	79	80	83	82	83	83	82	82	82	
	1500	78	79	80	81	81	81	81	81	80	
	1600	76	78	79	80	80	80	80	80	79	
	1700	75	77	78	79	79	79	79	79	78	
	1800	74	76	77	78	78	78	78	78	77	
	1900	73	75	76	77	77	77	77	77	76	
	2000	72	74	75	76	76	76	76	76	75	
	2100	72	73	74	75	76	76	75	75	74	
	2200	71	72	73	74	75	75	74	74	74	
	2300	70	71	72	73	74	74	74	73	73	
	2400	69	71	72	73	73	73	73	73	72	
	2500	69	70	71	72	72	72	72	72	71	
	2600	68	69	70	71	72	72	72	71	71	
	2700	67	69	70	71	71	71	71	70	70	
	2800	67	68	69	70	70	70	70	70	69	
	2900	66	67	68	69	70	70	70	69	69	
	3000	65	67	68	69	69	69	69	69	68	
	3200	64	66	67	68	68	68	68	67	67	
	3400	63	64	65	67	67	67	67	66	66	
	3600	62	63	64	66	66	66	66	65	65	
	3800	61	62	63	65	65	65	65	64	64	
	4000	60	62	63	64	64	64	64	64	63	
	4200	59	61	62	63	63	63	63	63	62	
	4400	59	60	61	62	62	62	62	62	61	
	4600	58	59	60	61	62	62	61	61	61	
	4800	57	58	59	60	61	61	61	60	60	
	5000	56	58	59	60	60	60	60	60	59	
	5500	55	56	57	58	59	59	58	58	57	
	6000	53	54	55	57	57	57	57	56	56	
	6500	52	53	54	55	56	56	55	55	54	
	7000	50	52	53	54	54	54	54	54	53	
	7500										
	8000										
	8500										
	9000										

표시범위에서의 사용은 벨트 수명이 단축되므로 피하여 주십시오.